

Cheat Sheet

Diffusion LED Strip

- SL1 = 1.5 W/ft
- SL3 = 3 W/ft
- SL4 = 3 W/ft
- SL5-RGB = 4.32 W/ft
- SL5-RGBW = 6 W/ft
- SL6 = 4.5 W/ft
- SL7.5 = 5 W/ft

- ✓ Every standard stock ribbon comes with a power feed on each end
- ✓ SL5-RGB use with four wires
- ✓ SL5-RGBW use with five wires



DLMULTI Drivers

- Dimmable LED Driver that works with Forward / Reverse phase, ELV, Triac or 0-10V Dimmers.
- Indoor/Outdoor
- High Efficiency
- Input Voltage : 100-277 VAC



Notes

- ✓ Dims
- ✓ Forward Phase
- ✓ Reverse Phase
- ✓ 0-10V
- ✓ Triac

Accessories Indoor Applications

- H8 Series use with SL1 & SL3 ribbon
- H10 Series use with SL6 ribbon
- S10 Series use with RGB ribbon
- RGBW12 Series use with RGBW ribbon
- SL4 and SL7.5 have no connectors, recommend ordering as custom.



SC-Connectors Series

- Diffusion SC-Connectors Series (SC10W01 & SC10W02) are designed to be used with SL6 Ribbon but will also work with SL1 and SL3 Ribbons.
- SC10W01 comes with 6" power feed.



Important Notes

- ✓ Max run length 32 ft
- ✓ To stay in class 2, 100W or less
- ✓ Distance between drivers and ribbon is based on voltage loss, do not go less than 22 volts