

SL-COB3 Outdoor Diffusion LED Ribbon



10W/M(3W/FT)
LED Watts

480/M(146/FT)
LED/Meter

91+
CRI

24V DC
Power Input



16 FT ROLL

CUSTOM CUT

Diffusion SL-COB3-Outdoor is a flexible 10mm wide COB LED Ribbon that delivers smooth, dot-free illumination. It is available in 16' rolls as well as custom cuts and can be cut every 50mm (2")

Lumens

2700K

800 lm/m
(243 lm/ft)

3000K

850 lm/m
(259 lm/ft)

4000K

1000 lm/m
(305 lm/ft)

Custom Kelvins available upon request



Specifications

Wattage	10 W/m (3 W/ft)	Max Run Length Product Limitation	16 ft
Voltage	24 Volts DC	Environment	Indoor and Outdoor
Roll Length	16 ft and Custom Cut	Suitability	Sauna Approved
Dimmable	Yes	Operating Temp	-40°C to 120°C
Lamp Life	50,000 hrs LM-80	IP Rating	IP67
CRI	91 + CRI	Cutting Point	2 in
Beam Angle	135°	Warranty	5 Year Warranty

Ordering Information

Ordering Code

Length

Voltage

Kelvin

SL-COB3-IN

XX

24V


XX

16 ft
CUSTOM CUT

2700K
3000K
4000K














Custom Kelvins available upon request

Diagram



SL-COB3 Outdoor Diffusion LED Ribbon

Common Pairings Channel

SLC-002S Slim Profile Channel  *Shows Dotting	SLC-007S 45 Degree Channel 	SLC-003R Ressed Channel 	SLC-402S Square Channel  *Connectors don't fit
SLC-011S Three Sided Lens Channel 	SLC-026F Sideways Flex Channel  *Only available for Custom Cut (Not field cuttable)	SLC-027F Up/Down Flex Channel  *Only available for Custom Cut (Not field cuttable)	SLC-034R Walk Over Channel 
SLC-037C Closet Rod Channel  Also Available as Suspended Luminaire	SLC-050SPWH Surface/Suspended Mount  *Dual Row Ribbon	SLC-065RWH Recessed Comes With Spring Clips  *Dual Row Ribbon	SLC - 090TWH Perimeter Cove Channel 
SLC-098KE Knife Edge Channel 			

*More Channel options available online

All Aluminum LED channels can be cut on-site using a miter saw equipped with a circular blade designed for cutting aluminum.

LED channels are sold separately. Refer to their respective spec sheets for additional details

[Visit LED Channel Catalog](#)

SL-COB3 Outdoor Diffusion LED Ribbon



LED Ribbon Wattage

10W/M(3W/FT)

LED Power Consumption

Residential

Total Watts Needed = (3 Watts Foot × Number of Feet) × 0.9

Commercial

Total Watts Needed = (3 Watts Foot × Number of Feet) × 0.8

Note: The max run length product limitation is 16'

Max distance of a driver is based on voltage loss calculation. Stay within 2% voltage loss

DLMULTI-024 Series Diffusion LED Driver

Specifications

Input Voltage	100-277 VAC	Environment	Indoor and Outdoor
Output Voltage	24V DC	Operating Temp	-40°C to 80°C
Dimming Range	0-100%	IP Rating	NEMA 4X
Dimmable	Yes	Warranty	5 Years

Product Title	Wattage	Output Current	Driver Dimension	Knock Outs
DLMULTI-024-30W Within Class 2	30W	1.25 A	165 mm L x 95 mm W x 26 mm H 6.49 in L x 3.75 in W x 1.02 in H	0.5 in (ID) Standard 1/2" won't fit Includes 2 Connectors
DLMULTI-024-60W Within Class 2	60W	2.5 A	188 mm L x 95 mm W x 26 mm H 7.40 in L x 3.75 in W x 1.02 in H	0.5 in (ID) Standard 1/2" won't fit Includes 2 Connectors
DLMULTI-024-100W Within Class 2	100W	4.16 A	220 mm L x 95 mm W x 41 mm H 8.66 in L x 3.75 in W x 1.61 in H	0.85 in (ID)
DLMULTI-024-150W Exceeds Class 2	150W	6.25 A	260 mm L x 104 mm W x 46 mm H 10.23 in L x 4.09 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-200W Exceeds Class 2	200W	8.33 A	260 mm L x 104 mm W x 46 mm H 10.23 in L x 4.09 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-300W Exceeds Class 2	300W	12.5 A	278 mm L x 110 mm W x 46 mm H 10.94 in L x 4.33 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-192W-2T Within Class 2	192W (2*96W)	2X 4.0 A	278 mm L x 110 mm W x 46 mm H 10.94 in L x 4.33 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-288W-3T Within Class 2	288W (3X 96W)	3X 4.0 A	303 mm L x 110 mm W x 46 mm H 11.93 in L x 4.33 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-384W-4T Within Class 2	384W (4X 96W)	4X 4.0 A	325 mm L x 140 mm W x 48 mm H 12.79 in L x 5.51 in W x 1.89 in H	0.85 in (ID)

Forward / Reverse Phase, ELV, TRIAC, or
0-10V Dimmers all in one LED Driver

