

SL3D-Bend RGBW

Diffusion LED Light



The Diffusion SL3D-Bend is a fully 360-degree bendable lighting system designed for curved applications. It includes mounting hardware and offers resistance to saline, acids, alkalis, corrosive gases, and UV rays. Rated for outdoor applications with an IP68 rating, it is submersible up to 9 meters.

Specifications

Wattage	19.58 W/m (6 W/ft)
Input Voltage	24V DC
Color Rendering Index (CRI)	91+ CRI
LED Qty	72/m (22/ft)
Lamp Life	50,000 hrs (LM-80)
Dimmable	Yes
Dimming Range	0-100%
Roll Length	Custom cut to order
Cutting Increment	41.67 mm (1.64")
Controls	Forward/Reverse Phase, ELV, TRIAC, 0-10V, DMX
Connections	Copper conductors, 20AWG
Mounting Material	Aluminum clips
Channel Material	Flexible opal channel
Top Bend Diameter	Ø300 mm (11.81 in)
Side Bend Diameter	Ø800 mm (31.49 in)
Max Run Length	10 M Run Lengths
Submersion	Rated for depths up to 9M
Installation Environment	Suitable for indoor and outdoor use
IP Rating	IP68 Rated
Operating Temperature	-20°C to 120°C
Impact Protection	IK10 Rated
UV Resistance	UV Stable
Corrosion Resistance	Saltwater tolerant
Certifications	cULus Listed (E486690)
Warranty	5 Year Warranty
Applications	Gardens, Walkways, Pools, Saunas, Fountains and Water Features


Ordering Information

Ordering Code	Wattage	Voltage	Length	Kelvin	Power Location
SL3D-BEND	XX 19.58 W/m (6 W/ft)	24V	XX CUSTOM CUT	RGBW	XX Left Outlet Right Outlet Straight Outlet Bottom Outlet

Lumens

Red 129 lm/m (39 lm/ft)	Green 216 lm/m (66 lm/ft)	Blue 28 lm/m (8.5 lm/ft)	(W)2700K 548 lm/m (167 lm/ft)


Diagram




SL3D-Bend

Diffusion LED Light


End Cap Outlet Direction




Wire With Anti-wicking Ferrule Diagram



Channel Options



Bend Radius



Top Bending Diameter
Ø300 mm (11.81 in)

Side Bending Diameter
Ø800 mm (31.49 in)