

SL7.3-Indoor Diffusion LED Ribbon




10W/M(3W/FT)
LED Watts

276/M(84/FT)
LED/Meter

95+
CRI

24V DC
Power Input



CUSTOM CUT ONLY

The Diffusion SL7.3 Indoor is a high-fidelity flexible 10 mm wide linear LED strip. It is only available in custom cut that can be cut every 7 LEDs (25 mm or 1 in)

Custom lengths available upon request

Lumens

2700K 928 lm/m (282 lm/ft)	3000K 970 lm/m (295 lm/ft)	3400K 1013 lm/m (308 lm/ft)	4100K 1055 lm/m (321 lm/ft)
---	---	--	--

Custom Kelvins available upon request



Specifications


Wattage	10 W/m (3 W/ft)	Max Run Length for Class 2	27 ft
Voltage	24 Volts DC	Max Run Length Product Limitation	32 ft
Roll Length	Custom Cut Only	Operating Temp	-40°C to 120°C
Dimmable	Yes	Cutting Point	1 in
Lamp Life	50,000 hrs LM-80	Adhesive	3M Double Coated
CRI	95 + CRI	Warranty	5 Year Warranty

Ordering Information

Ordering Code	Length	Voltage	Kelvin
SL7.3 - IN	XX CUSTOM CUT ONLY	24V	XX 2700K 3000K 3400K 4100K














Custom Kelvins available upon request

Diagram



SL7.3-Indoor Diffusion LED Ribbon

Common Pairings Channel

SLC-002S Slim Profile Channel  *Shows Dotting	SLC-007S 45 Degree Channel 	SLC-003R Ressed Channel 	SLC-402S Square Channel  *Connectors don't fit
SLC-011S Three Sided Lens Channel 	SLC-026F Sideways Flex Channel  *Only available for Custom Cut (Not field cuttable)	SLC-027F Up/Down Flex Channel  *Only available for Custom Cut (Not field cuttable)	SLC-034R Walk Over Channel 
SLC-037C Closet Rod Channel  Also Available as Suspended Luminaire	SLC-050SPWH Surface/Suspended Mount  *Dual Row Ribbon	SLC-065RWH Recessed Comes With Spring Clips  *Dual Row Ribbon	SLC - 090TWH Perimeter Cove Channel 
SLC-098KE Knife Edge Channel 			

*More Channel options available online

All Aluminum LED channels can be cut on-site using a miter saw equipped with a circular blade designed for cutting aluminum.

LED channels are sold separately. Refer to their respective spec sheets for additional details

[Visit LED Channel Catalog](#)

SL7.3-Indoor Diffusion LED Ribbon



LED Ribbon Wattage

10W/M(3W/FT)

LED Power Consumption

Residential

Total Watts Needed = (3 Watts Foot × Number of Feet) × 0.9

Commercial

Total Watts Needed = (3 Watts Foot × Number of Feet) × 0.8

Note: Maximum run length is 27' to stay in Class 2

Max distance of a driver is based on voltage loss calculation. Stay within 2% voltage loss

DLMULTI-024 Series Diffusion LED Driver

Specifications

Input Voltage	100-277 VAC	Environment	Indoor and Outdoor
Output Voltage	24V DC	Operating Temp	-40°C to 80°C
Dimming Range	0-100%	IP Rating	NEMA 4X
Dimmable	Yes	Warranty	5 Years

Product Title	Wattage	Output Current	Driver Dimension	Knock Outs
DLMULTI-024-30W Within Class 2	30W	1.25 A	165 mm L x 95 mm W x 26 mm H 6.49 in L x 3.75 in W x 1.02 in H	0.5 in (ID) Standard 1/2" won't fit Includes 2 Connectors
DLMULTI-024-60W Within Class 2	60W	2.5 A	188 mm L x 95 mm W x 26 mm H 7.40 in L x 3.75 in W x 1.02 in H	0.5 in (ID) Standard 1/2" won't fit Includes 2 Connectors
DLMULTI-024-100W Within Class 2	100W	4.16 A	220 mm L x 95 mm W x 41 mm H 8.66 in L x 3.75 in W x 1.61 in H	0.85 in (ID)
DLMULTI-024-150W Exceeds Class 2	150W	6.25 A	260 mm L x 104 mm W x 46 mm H 10.23 in L x 4.09 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-200W Exceeds Class 2	200W	8.33 A	260 mm L x 104 mm W x 46 mm H 10.23 in L x 4.09 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-300W Exceeds Class 2	300W	12.5 A	278 mm L x 110 mm W x 46 mm H 10.94 in L x 4.33 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-192W-2T Within Class 2	192W (2*96W)	2X 4.0 A	278 mm L x 110 mm W x 46 mm H 10.94 in L x 4.33 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-288W-3T Within Class 2	288W (3X 96W)	3X 4.0 A	303 mm L x 110 mm W x 46 mm H 11.93 in L x 4.33 in W x 1.81 in H	0.85 in (ID)
DLMULTI-024-384W-4T Within Class 2	384W (4X 96W)	4X 4.0 A	325 mm L x 140 mm W x 48 mm H 12.79 in L x 5.51 in W x 1.89 in H	0.85 in (ID)

Forward / Reverse Phase, ELV, TRIAC, or
0-10V Dimmers all in one LED Driver

