

DIFFUSION

by **RJCROSS**
architectural products ltd.

lighting



Follow us on Instagram

1

BIN SELECTION

No two LED's can be exactly the same causing major issues with LED light output and color. This is why some products have large variations in color consistency. At Diffusion Lighting we use a One Bin Selection, meaning that all of our LEDs must fit within our extremely tight parameters in order to be included in our line. Most manufactures stay away from a One Bin Selection to save money or they charge a premium. This is just another reason Diffusion Lighting is set apart from their competition. We keep the price competitive, but do not sacrifice the quality.

2

STEP MACADAM ELLIPSE

MacAdam Ellipse is a region on a chromaticity diagram which contains all colors which are indistinguishable, to the average human eye, from the color at the center of the ellipse. The contour of the ellipse therefore represents the just noticeable differences of chromaticity. In simpler terms MacAdam Ellipse was developed to determine boundaries around target color points on the CIE chromaticity diagram whereby the source can deviate before the observer can perceive a difference in target color. MacAdam Ellipses were evolved to describe the "steps", which define standard deviations from the target point in all color directions. ANSI recommends that light engine manufactures stay within a "4 step" ellipse. We surpass ANSI's recommendations and most of our competitors in the market place with our 2 step MacAdam Ellipse.

3

TEST QUALITY CONTROL

At Diffusion Lighting we strive to keep our quality to the highest standards we can. So we have developed a 3Test Quality Control that happens from start to finish. This means that our LEDs get tested 3 times while our product is being constructed to ensure the end result is flawless. Our LEDs get thoughtfully tested after originally being manufactured, get tested after being installed on our custom PCB board and finally get tested one last time before anything ships out. This process ensures your product is exactly what you expected and will match from one batch to the other.

5

Year Warranty

Here at Diffusion LED Lighting we truly stand behind our product. We offer an outstanding 5 year warranty and work extremely hard to make sure you and your customer are happy. In some cases we have even been known to warranty issues that are not even a result of Diffusion.

SL1 - Indoor Diffusion LED Strip

Description

Diffusion SL-1 is a flexible 8mm wide linear LED strip. It is available in 16' and 100' rolls that can be cut every 6 LEDs (100mm or 4").

Features

- 3M industrial strength adhesive tape
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll

Custom lengths available upon request


Specifications

- LED : 4.8 W/m (1.5W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 60/m (18/ft)
- Power Input : 24V DC
- CRI > 91

Lumens

- 2700K = 394 lm/m (120 lm/ft) ●
- 3000K = 416 lm/m (126 lm/ft) ●
- 3400K = 438 lm/m (132 lm/ft) ○
- 4100K = 460 lm/m (140 lm/ft) ○

Custom Kelvins available upon request



ORDERING
CODE

LENGTH

VOLTAGE

KELVIN

SL1-IN	xx	24V	xxxx
--------	----	-----	------

SL1-IN

16 ft
100 ft

24 Volt

2700 K
3000 K
3400 K
4100 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL1 - Outdoor Diffusion LED Strip

Description

Diffusion SL-1 is a flexible 10mm wide linear LED strip. It is available in 16' and 32' rolls that can be cut every 6 LEDs (100mm or 4").

Features

- Includes endcaps and mounting clips with screws
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll
- IP67

Custom lengths available upon request


Specifications

- LED : 4.8 W/m (1.5W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 60/m (18/ft)
- Power Input : 24V DC
- CRI > 91

Lumens

- 2700K = 394 lm/m (120 lm/ft) ●
- 3000K = 416 lm/m (126 lm/ft) ●
- 3400K = 438 lm/m (132 lm/ft) ●
- 4100K = 460 lm/m (140 lm/ft) ○

Custom Kelvins available upon request



ORDERING
CODE

LENGTH

VOLTAGE

KELVIN

SL1-OUT

xx

24V

xxxx

SL1-OUT

16 ft
32 ft

24 Volt

2700 K
3000 K
3400 K
4100 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL3 - Indoor Diffusion LED Strip

Description

Diffusion SL-3 is a flexible 8mm wide linear LED strip. It is available in 16' and 100' rolls that can be cut every 6 LEDs (50mm or 2").

Features

- 3M industrial strength adhesive tape
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll

Custom lengths available upon request



Specifications

- LED : 10 W/m (3 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 120/m (36/ft)
- Power Input : 24V DC
- CRI > 91

Lumens

- 2700K = 788 lm/m (236 lm/ft) ●
- 3000K = 832 lm/m (249 lm/ft) ●
- 3400K = 876 lm/m (263 lm/ft) ●
- 4100K = 908 lm/m (279 lm/ft) ○

Custom Kelvins available upon request



ORDERING
CODE

SL3-IN

LENGTH

xx
16 ft
100 ft

VOLTAGE

24V
24 Volt

KELVIN

xxxx
2700 K
3000 K
3400 K
4100 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL3 - Outdoor Diffusion LED Strip

Description

Diffusion SL-3 is a flexible 10mm wide linear LED strip. It is available in 16' and 32' rolls that can be cut every 6 LEDs (50mm or 2").

Features

- Includes endcaps and mounting clips with screws
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll
- IP67

Custom lengths available upon request

Specifications

- LED : 10 W/m (3 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 120/m (36/ft)
- Power Input : 24V DC
- CRI > 91

Lumens



2700K = 788 lm/m (236 lm/ft) ●

3000K = 820 lm/m (252 lm/ft) ●

3400K = 876 lm/m (263 lm/ft) ●

4100K = 908 lm/m (279 lm/ft) ○

Custom Kelvins available upon request



ORDERING
CODE

SL3-OUT

LENGTH

xx

VOLTAGE

24V

KELVIN

xxxx

SL3-OUT

16 ft
32 ft

24 Volt

2700 K
3000 K
3400 K
4100 K

1 BIN SELECTION

2 STEP MACADAM ELLIPSE

3 TEST QUALITY CONTROL



SL4 - Indoor Diffusion LED Strip

Description

Diffusion SL-4 is a flexible 5mm wide side mount linear LED strip. It is available in 16' rolls that can be cut every 6 LEDs (50mm or 2").

Features

- 3M industrial strength adhesive tape
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll

Custom lengths available upon request

Specifications


- LED : 10 W/m (3 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 120/m (36/ft)
- Power Input : 24V DC
- CRI > 91

Lumens

3000K = 728 lm/m (222 lm/ft) ●

4000K = 812 lm/m (247 lm/ft) ○

Custom Kelvins available upon request



ORDERING CODE	LENGTH	VOLTAGE	KELVIN
SL4-IN	xx	24V	xxxx
SL4-IN	16 ft	24 Volt	3000 K
			4000 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL4 - Outdoor Diffusion LED Strip

Description

Diffusion SL-4 is a flexible 8mm wide side mount linear LED strip. It is available in 16' and 32' rolls that can be cut every 6 LEDs (50mm or 2").

Features

- Includes endcaps and mounting clips with screws
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll
- IP67

Custom lengths available upon request

Specifications


- LED : 10 W/m (3 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 120/m (36/ft)
- Power Input : 24V DC
- CRI > 91

Lumens

3000K = 728 lm/m (222 lm/ft) ●

4000K = 812 lm/m (247 lm/ft) ○

Custom Kelvins available upon request



ORDERING
CODE

LENGTH

VOLTAGE

KELVIN

SL4-OUT

xx

24V

xxxx

SL4-OUT

16 ft
32 ft

24 Volt

3000 K
4000 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL5-RGB(W) Indoor Diffusion LED Strip

Description

Diffusion SL5-RGB is a flexible 10mm wide linear LED strip. Diffusion SL5-RGBW is a flexible 12mm wide linear LED strip. Both are available in 16' and 100' rolls that can be cut every 6 LEDs (100mm or 4").

Features

- 3M industrial strength adhesive tape
- Long life LED : 50,000 hrs
- 2' power feeds on both ends of every roll

Custom lengths available upon request

Specifications


- RGB LED : 14.4 W/m (4.32 W/ft)
- RGBW LED : 19.2 W/m (6 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 60/m (18/ft)
- Power Input : 24V DC

Lumens

RGB = Up to 591 lm/m (180 lm/ft)



W(2700K) = Up to 400 lm/m (122 lm/ft)



ORDERING
CODE

LENGTH

VOLTAGE

KELVIN

SL5-IN	xx	24V	xxxx
SL5-IN	16 ft 100 ft	24 Volt	RGB RGBW

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL5-RGB(W) Outdoor Diffusion LED Strip

Description

Diffusion SL5-RGB is a flexible 12mm wide linear LED strip. Diffusion SL5-RGBW is a flexible 14mm wide linear LED strip. Both are available in 16' and 32' rolls that can be cut every 6 LEDs (100mm or 4").

Features

- Includes endcaps and mounting clips with screws
- Long life LED : 50,000 hrs
- 2' power feeds on both ends of every roll
- IP67

Custom lengths available upon request

Specifications


- RGB LED : 14.4 W/m (4.32 W/ft)
- RGBW LED : 19.2 W/m (6 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 60/m (18/ft)
- Power Input : 24V DC

Lumens

RGB = Up to 591 lm/m (180 lm/ft)



W(2700K) = Up to 400 lm/m (122 lm/ft)



ORDERING CODE

CODE	LENGTH	VOLTAGE	KELVIN
SL5-OUT	xx	24V	xxxx
SL5-OUT	16 ft 32 ft	24 Volt	RGB RGBW

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL6 - Indoor Diffusion LED Strip

Description

Diffusion SL-6 is a flexible 10mm wide linear LED strip. It is available in 16' and 100' rolls that can be cut every 6 LEDs (50mm or 2").

Note: SL6 needs to be installed in aluminum channel

Features

- 3M industrial strength adhesive tape
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll

Custom lengths available upon request


Specifications

- LED : 14.4 W/m (4.5 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 120/m (36/ft)
- Power Input : 24V DC
- CRI > 91

Lumens

- 2700K = 1220 lm/m (366 lm/ft) ●
- 3000K = 1282 lm/m (384 lm/ft) ●
- 3400K = 1344 lm/m (402 lm/ft) ●
- 4100K = 1400 lm/m (420 lm/ft) ○

Custom Kelvins available upon request



ORDERING CODE	LENGTH	VOLTAGE	KELVIN
SL6-IN	xx	24V	xxxx
SL6-IN	16 ft	24 Volt	2700 K
	100 ft		3000 K
			3400 K
			4100 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL6 - Outdoor Diffusion LED Strip

Description

Diffusion SL-6 is a flexible 12mm wide linear LED strip. It is available in 16' and 32' rolls that can be cut every 6 LEDs (50mm or 2").

Features

- Includes endcaps and mounting clips with screws
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 2' power feeds on both ends of every roll
- IP67

Custom lengths available upon request

Specifications

- LED : 14.4 W/m (4.5 W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 120/m (36/ft)
- Power Input : 24 VDC
- CRI > 91

Lumens



2700K = 1220 lm/m (366 lm/ft) ●

3000K = 1282 lm/m (384 lm/ft) ●

3400K = 1344 lm/m (402 lm/ft) ●

4100K = 1400 lm/m (420 lm/ft) ○

Custom Kelvins available upon request



ORDERING CODE	LENGTH	VOLTAGE	KELVIN
SL6-OUT	xx	24V	xxxx
SL6-OUT	16 ft 32 ft	24 Volt	2700 K 3000 K 3400 K 4100 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL7.5 - Indoor Diffusion LED Strip

Description

Diffusion LED Strip SL7.5 is a flexible 10mm wide linear LED strip. It is only available in custom cut and can be cut every 7 LEDs (25mm or 1").

Note: SL7.5 needs to be installed in aluminum channel

Features

- 3M industrial strength adhesive tape (included)
- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 24" leads on both ends of each roll

Custom lengths recommended


Specifications

- LED : 16.4 W/m (5W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 252/m (77/ft)
- Power Input : 24V DC
- CRI > 95
- R values all over 95


Lumens

- 2700K = 1576 lm/m (472 lm/ft) ●
- 3000K = 1680 lm/m (504 lm/ft) ●
- 3400K = 1800 lm/m (540 lm/ft) ●
- 4100K = 1936 lm/m (580 lm/ft) ○

Custom Kelvins available upon request



Must order in custom cuts
No connectors for SL7 series



ORDERING CODE	LENGTH	VOLTAGE	KELVIN
SL7.5-IN	xx	24V	xxxx
SL7.5-IN		24 Volt	2700 K
			3000 K
			3400 K
			4100 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SL7.5 - Outdoor Diffusion LED Strip

Description

Diffusion LED Strip SL7.5 is a flexible 12mm wide linear LED strip. It is only available in custom cut and can be cut every 7 LED chips (25mm/1").

Note: SL7.5 needs to be installed in aluminum channel

Features

- Long life LED : 50,000 hrs
- Dimmable with dimming power supply
- 24" leads on both ends of each roll
- IP 65

Custom lengths recommended

Specifications

- LED : 14.4 W/m (4.5W/ft)
- Lamp Life : 50,000 hrs LM80
- LED/Meter : 252/m (77/ft)
- Power Input : 24V DC
- CRI > 95
- R values all over 95


Lumens

- 2700K = 1418 lm/m (425 lm/ft) ●
- 3000K = 1512 lm/m (453 lm/ft) ●
- 3400K = 1620 lm/m (486 lm/ft) ●
- 4100K = 1742 lm/m (522 lm/ft) ○

Custom Kelvins available upon request



Must order in custom cuts



ORDERING CODE	LENGTH	VOLTAGE	COLOUR
SL7.5-OUT	XX	24V	XXXX
SL7.5-OUT		24 Volt	2700 K
			3000 K
			3400 K
			4100 K

- 1 BIN SELECTION
- 2 STEP MACADAM ELLIPSE
- 3 TEST QUALITY CONTROL



SLC-002S

Description

Low profile, anodized aluminum channel that comes complete with three clear mounting clips, two grey endcaps, and an opal polycarbonate lens.

Extra clips and endcaps available by request.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)
- Color : Silver, White, Black

Custom color available.

Applications

- Coves
- Top kitchen cabinet
- Wardrobe
- Shelving
- Closets

If seen directly or through a reflective surface, not recommended unless used with SL7.5


NEW FLAT LENS (Standard on every order)

If you need Old Round Lens please specify when ordering




Shows Dotting unless used with high fidelity SL7 Series ribbon.



Channel



End Caps



Mounting Clips



ORDERING
CODE

SLC-002S

COLOR

SLC-002S

Blank (Silver)
WH
BK

Custom RAL color upon request.

SLC-003R

Description

Recessed, anodized aluminum channel that comes complete with three clear mounting clips, two grey endcaps, and an opal polycarbonate lens.

Extra clips and endcaps available by request.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)
- Color : Silver, White, Black


Custom color available.

Applications


- Drywall
- Wall surfaces
- Kitchen cabinet
- Shelving
- Furniture
- Recess





Channel



End Caps



Mounting Clips



ORDERING
CODE

COLOR



SLC-003R

Blank (Silver)
WH
BK

Custom RAL color upon request.

SLC-007S

Description

45 degree, anodized aluminum channel that comes complete with three clear mounting clips, two grey endcaps, and an opal polycarbonate lens.

Extra clips and endcaps available by request.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant,
- UV stable, shatter resistant
- Length : 8' (2.44 meters)
- Color : Silver, White, Black


Custom color available.

Applications


- Coves
- Kitchen cabinet
- Wardrobe
- Shelving





Channel



End Caps



Mounting Clips



ORDERING
CODE

SLC-007S

SLC-007S

COLOR

Blank (Silver)
WH
BK

Custom RAL color upon request.

SLC-402S

Description

Narrow anodized aluminum channel that comes complete with mounting hardware, two grey endcaps and extra thick opal polycarbonate lens for zero dotting.

Extra clips and endcaps available by request.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant, UV stable, shatter resistant.
- Length : 8' (2.44 meters)
- Color : Silver, White, Black


Custom color available.

Applications


- Platforms
- Shelving
- Niches
- Stairs
- Furniture





Channel



End Caps



Mounting Clips



ORDERING
CODE

COLOR

SLC-402S

SLC-402S

Blank (Silver)
WH
BK

Custom RAL color upon request.

SLC-011S

Description

Two part anodized aluminum channel that comes complete with two grey endcaps and an opal polycarbonate lens.

Extra endcaps available by request.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)
- Color : Silver, White, Black


Custom color available.

Applications



- Behind mirrors
- Surface mount
- Kitchen cabinet
- Wardrobe
- Shelving
- Closets



Channel



End Caps



ORDERING
CODE

COLOR

SLC-011S

SLC-011S

Blank (Silver)
WH
BK

Custom RAL color upon request.

SLC-012T

Description

Trimless anodized aluminum channel that comes complete with two aluminum endcaps and an opal polycarbonate lens.


Extra clips and endcaps available by request.

Specifications


- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)

Applications



- Drywall
- Flanges can be cut off and installed in wood



Channel



End Caps



SLC-026F

Description

Sideways flexible channel that comes complete with mounting hardware for curved application.

Extra clips and endcaps available by request.

Specifications

- Channel : Flexible opal channel
- Note : Inner dimension is approx 11mm and can accommodate SL1, SL3, SL4, SL6 & RGB indoor ribbon
- Length : Cut to suit
- Note : Minor color shift in this channel
- IP67


Custom cut made to order.

Applications


- Gardens
- Walkways
- Exterior and, or Interior use
- Curved applications
- Behind circle mirrors
- Curved windows





Channel



End Caps



Mounting Clips



SLC-034R

Description

In-floor anodized aluminum channel that comes complete with two grey endcaps and a 3mm thick opal polycarbonate lens.

Extra endcaps available by request.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : 3mm thick opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)
- Color : Silver, White, Black

Walk over rated.


Applications

- Walk ways
- Driveways
- Exterior and, or Interior use
- Stairs
- Niches





Use outdoor ribbon for exterior or walk over applications.

Channel



End Caps



ORDERING
CODE

SLC-034R

COLOR

SLC-034R

Blank (Silver)
WH
BK

Custom RAL color upon request.

SLC-037C

Description

Anodized aluminum closet rod that comes with a 1.25mm thick opal polycarbonate lens for zero dotting.

*Weight limit is depending on what the end caps are being mounted to.
Closet rod on its own can handle 50KG/ft*.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : 1.25mm thick opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)
- End fittings and center supports sold separately.
- Color : Silvery, White, Black


Custom color available.

Applications


- Closets
- Suspended fixture - with modified components (email for more information)

IMAGE
COMING SOON



Channel



End Caps E37C (Order Separately)



Center Support C37C (Order Separately)



ORDERING
CODE

SLC-037C

COLOR

SLC-037C

Blank (Silver)
WH
BK

Custom RAL color upon request.

SLC-050SP

Description

Surface/Pendant mount Aluminum extrusion with opal polycarbonate lens.

Extra clips and endcaps available by request.

Specifications

- Dimensions : 50mm W x 43mm D
- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)
- Color : White or Black

Dual Row LED required


Applications

- Surface mount
- Suspended fixture
- Halls
- Workshops
- Libraries
- Restaurants




Optional suspension kits are available.

Channel





End Caps






Mounting Clips

• Surface Mounting Clips



• Wall Mounting Clips



ORDERING
CODE

SLC-050SP

SLC-050SP

COLOR

WH
BK

Custom RAL color upon request.

SLC-065R

Description

Recessed mount aluminum extrusion with opal polycarbonate lens.

Extra clips and endcaps available by request.

Specifications

- Channel : Anodized aluminum extrusion
- Lens : Opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Length : 8' (2.44 meters)
- Mounting : Recess mounting springs
- Color : White or Black


Dual Row LED required

Applications


- Halls
- Workshops
- Ballrooms
- Recessed into drywall
- Doctors offices
- Classrooms





Channel



End Caps



Mounting Clips



ORDERING
CODE

SLC-065R

SLC-065R

COLOR

WH

BK

Custom RAL color upon request.

SLC-098KE

Description


Anodized aluminum knife edge profile (Joiners & acrylic lenses sold separately)

Specifications



- Channel : Anodized aluminum extrusion
- Lens : Two different acrylic lenses available upon request
- Length : 8' (2.44 meters)

Applications

- Edgeless coves



Channel



• Lens



• 45° Vertical Joiner



• 45° Horizontal Joiner



• 90° Vertical Joiner



• 90° Horizontal Joiner



• Straight Joiner



Perch

Description

Diffusion Perch Series is a full 360 degree illumination with no shadows throughout. It comes up to 9w/ft approx 900 lumens per foot.


Applications

- Suspended fixture
- Halls
- Ballrooms
- Libraries
- Restaurants

Features

- Lens : 2.3" Diameter, Opal polycarbonate, high heat resistant, UV stable, shatter resistant
- Suspended Vertically or Horizontally
- Can be joined together with joiners to create longer runs up to an infinite length
- Perch 360°
√ 6 Runs LED Ribbon, up to 900 lm/ft
- Perch 180° Up
√ 3 Runs LED Ribbon Up, up to 450 lm/ft
- Perch 180° Down
√ 3 Runs LED Ribbon Down, up to 450 lm/ft

Optional Suspension Kits are available



Fixture	Orientation	Models	Fixture length	Suspension length	Suspension Kits
Perch	xx	xx	xx	xx	xx
	VER HORZ	360 ° 180 ° Down 180 ° Up	Up to 8' without Joiner More than 8' with Joiners	xx/ft	JB-5-SG (WH/BK/NK) TB-2-LG (WH/BK/NK) WC-2-SG (WH/BK/NK) CT-SG (NK)

DLMULTI-024-SERIES Triac/0/10V (5 in 1) Dimmable Driver

Description

Diffusion DLMULTI-024-Series are Dimmable LED Driver that works with Forward / Reverse phase, ELV, Triac or 0-10V Dimmers.

Features

- Protection from short circuit, over current and over voltage
- Internal self reset mini breakers
- Compatible with virtually every style dimmer
- Flicker-free ~ 20,000 Hz
- Indoor/Outdoor
- High Efficiency
- Working Temp : -40 ~ +85° C
- Wet location rated

Specifications

- Input Voltage : 100-277 VAC
- Output Voltage : 24 VDC
- Dimming Range : 0-100%


0% with select dimmers only

Available Wattages


30W / 60W / 100W / 150W
200W / 300W



Comes with two Connectors for 30W and 60W ONLY



Only takes up to 14/2 loomex or 14/3 sjoow



DLND-024V-(18W36W) Electronic Non-Dimmable Driver

Description

Diffusion DLND-024V-(18W/36W) is an electronic, non-dimmable driver in a plastic enclosure.

Features

- No junction box required
- 18W or 36W
- IP40 rating

Rated for indoor use only

Specifications

DLND-024V-18W

- Input : 120V
- Output : 24 VDC
- Output Current : 0.75A
- Dimensions :
4.5" L x 1.75" W x 1.125" H

DLND-024V-36W

- Input : 120V
- Output : 24 VDC
- Output Current : 1.5A
- Dimensions :
5.5" L x 1.75" W x 1.125" H



Plug-In Driver

Description

Diffusion Plug-in drivers are available in 24W and 60W.

Features

- Simple plug and play setup
- cUL Listed

Specifications

- Input : 120V
- Plug-in with 2.1mm jack
- 2.1mm female jack included

• PD60-24V



• PW24-24V



SC-Connectors Series

Description

Diffusion SC-Connectors Series are designed to be used with SL6 Ribbon but will also work with SL1 and SL3 Ribbons.

Features

- Solderless connections
- Can be used as power feed by using your own cable
- Come with a Screwdriver


Specifications

- SC10W01 comes with 6" power feed.
- Dimensions
10.2mm L x 10.0mm W x 7.7mm H
0.40" L x 0.39" W x 0.30" H

SC10W01



SC10W02



Accessories Indoor Applications

Description

Diffusion clip connectors are designed to be user friendly and versatile enough to be used in almost any indoor application.

Features

- Solderless connections
- Clips closed and firmly holds the ribbon in place
- No special connectors or hardware required

Specifications

H8 SERIES

8mm inner width used with SL1 & SL3 ribbon

H10 SERIES

10mm inner width used with SL6 ribbon

S10 SERIES

10mm inner width used with RGB ribbon

RGBW12 SERIES

12mm inner width used with RGBW ribbon

Power Feeds



H8W1



H10W1



S10W1



RGBW14W1

6" Connectors



H8W2



H10W2



S10W2



RGBW12W2

Butt Connectors



H8W0



H10W0



S10W0



RGBW12W0

Micro Sensors and Switches Inline Channel Mounted

Description

Four unique sensors that can work inline, remote and/or be built into the channel itself.

Specifications

- Input Voltage : 24 VDC
- Loading Power : 8A Max

Features

- Micro push button on/off only
- Touch with dimming and memory
- Proximity (swipe hand near sensor) on/off only
- PIR timed 6-70s

Custom pre-installation assembly available upon request

Measurements

- CRTB01 : 17.3mm x 75mm
- CRTT03 : 17.3mm x 75mm
- CRTSPIRT : 17.3mm x 75mm
- CRTS01 : 17.3mm x 75mm

CRTB01 - Micro Button Switch

One touch on/off switch



CRTT03 - Dimming Touch Switch

Blue light identifying where to touch to control,
Hold to dim on/off



CRTS01 - Proximity Hand Sensor

on/off function only
Swipe hand past sensor to active



CRTSPIRIT - PIR Motion Sensor

Adjustable timer controlling the length of time the lights stay on from 6 to 70 seconds



Switched Dimmable Touch Sensor

Description

Switched Dimmable Touch Sensor offering solutions to a wide range of applications.

Specifications

- Input Voltage : 24 VDC
- Loading Power : 8A Max

Features

- Flush circular dimmable touch switch with memory (offered in black and white)

CRTT04B / CRTT04W - Dimming Touch Switch

Dimensions : 22mm diameter (Hole required is 18mm diameter)

Flush circular dimmable touch switch

Available in black and white



CRTSIRDH Door/Hand sensor

Description


Door/Hand sensors offering solutions to a wide range of applications.

Specifications

- Input Voltage : 12-24 VDC
- Loading Power : 4A Max

Features

- Interchangeable door/hand operated multi sensor switch
- Detection Range : < 10cm
- Available in Black and White



RGB(W) Remote & Controller

Description

Diffusion M8 & M4 Remote & Controller are capable of controlling up to 10 different controllers at once at a distance of up to 50m away (unobstructed distance).

Features

- Designed to control multiple sections of RGB(W) ribbon lighting from a single remote
- Interchangeable with both remotes
- Wall mountable

Specifications

- Power Input : 24 VDC
- Max Current Load : 5A x 4 CH (Max 20A)
- Max Output Power : 480W @ 24V
- GreyScale Max :
4096 x 4096 x 4096 x 4096

• M4 +M4 - 5A



• M8 +M4 - 5A



UX8 RGB(W) Wall Mount Touch Panel

Description

Diffusion UX series touch panels are wall mountable and DMX controlled.

Features

- Easy install and remove design
- 8A per channel max 24A
- With audible buttons which can also be turned off
- Various modes, speed, dimming and multi zone control
- User programmable colour modes

Specifications

- UX8 Wall Unit
- Power Input : 24 VDC
- Output : Control wire to DMX controller

Dimensions :

3.38" L x 3.38" W x 1.41" H

86mm L x 86mm W x 36mm H





5

Year Warranty

Limited 5 year warranty

RJcross Architectural Products Ltd ("We", "us" or "Seller") warrant Diffusion LED products and accessory(s) ("Diffusion Lighting") to be free from defects in materials and workmanship, and to operate from the date of installation (or date of manufacture if installation date is not known or available or verifiable) for a period of five (5) years. If a Diffusion Lighting Product fails to operate during the warranty period, we will repair or replace, at our discretion, the Diffusion Lighting Product in accordance with our Terms and Conditions. (labor is not included)